

# Church Lights



## Church Lighting

Cole offers Church Lights that provide efficient illumination combined with elegant designs and quality construction. Fixtures are available as chain or stem mounted chandeliers, wall sconces, and surface ceiling luminaires. All fixtures are provided with white acrylic diffusers and medium or dark metallic bronze polyester finishes standard. Several finish, diffuser, and accessory options are available to tailor fixtures to particular job requirements.

Modified or custom Church Lights may also be developed to meet your exact specifications. To learn more about our custom capabilities and comprehensive range of standard lighting fixtures, call us directly or contact your local Cole representative.

**COLE**  
*Lighting*

**C.W. Cole & Company, Inc.**  
2560 Rosemead Boulevard  
South El Monte, CA 91733-1593

Tel. (626) 443-2473  
Fax (626) 443-9253  
info@colelighting.com  
[www.colelighting.com](http://www.colelighting.com)

## 160 Series

### Description

Stem or chain-suspended, wall and ceiling mounted, Gothic or Romanesque-inspired hexagonal fixtures are available in several mounting configurations to allow a consistent design theme as various illumination needs are addressed. Multiple output options are available to meet job requirements. A variety of trim options are available that can be carried across the various models. Dimming capabilities available on all models.

These models can also be customized beyond the options illustrated to meet specific design goals.

### Features

Diffusers are .125" white acrylic. Other diffuser colors, textures, and materials are available. The finish is medium or dark metallic bronze textured powder coat polyester. Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%). LED options include E26/medium base, standard output and high output modules. 120V-277V electronic drivers are standard universal voltage. Mounting plate above canopy mounts to ceiling structure and covers junction box.



18"W x 60"H (457 x 1524mm)



18"W x 36"H (457 x 914mm)

**Gothic**  
*illustrated*



Hexagon 24" across points x 9-1/2"H (610 x 241mm)



8-1/2"W x 16"H (216 x 406mm)



14" dia W x 36"H (356 x 914mm)



14" dia W x 60"H (356 x 1524mm)

## 170 Series

### Description

These simple cylindrical fixtures provide an even luminous surface highlighted by vertical wood accent elements. Steel channels may be substituted for the wood, or the accents can be deleted. Pendant, wall, and surface ceiling mounted versions are offered. Wall and ceiling versions of this design are available.

### Features

Diffusers are .125" white acrylic and canopy is 20 gauge steel. Other diffuser colors, textures, and materials are available. The finish on canopy and stem is medium or dark metallic bronze textured powder coat polyester. The wood accents are stained golden oak unless otherwise specified. Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%). LED options include E26/medium base, standard output and high output modules. 120V-277V electronic drivers are standard universal voltage. Optional downlight has concentric louver assembly below for glare control. Mounting plate above canopy mounts to ceiling structure and covers junction box.



10-1/4" dia W x 16"H (260 x 406mm)



22" across points x 7-1/2"H (559 x 191mm)

## 180 Series



14" dia W x 36"H (356 x 914mm)



14" dia W x 60"H (356 x 1524mm)

### Description

These cylindrical fixtures provide an even luminous surface with top and bottom banding, with or without vertical wood accent elements. Steel channels may be substituted for the wood, or the accents can be deleted. Pendant, wall, and surface ceiling mounted versions are offered.

### Features

Diffusers are .125" white acrylic. Other diffuser colors, textures, and materials are available. The finish is medium or dark metallic bronze polyester. LED options include E26/medium base, standard output and high output modules. Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%). 120V-277V electronic drivers are standard universal voltage. Optional downlight has concentric louver assembly below for glare control. Mounting plate above canopy mounts to ceiling structure and covers junction box. Loop on stem meets seismic requirements.



8-11/16" dia W x 16"H (221 x 406mm)



22" across points x 7 1/2"H (559 x 191mm)



*Typical Religious Symbols*

**COLE**  
*Lighting*

C.W. Cole & Company, Inc.  
2560 Rosemead Boulevard  
South El Monte, CA 91733-1593

Tel. (626) 443-2473  
Fax (626) 443-9253  
info@colelighting.com  
[www.colelighting.com](http://www.colelighting.com)