

## CH 160 Series

### Construction

- Fixture body and canopy are 20 gauge steel
- Flat diffuser provided in bottom unless other options are selected
- Diffusers are .125" white acrylic; other colors, textures, and materials are available
- Finish is textured powder coat polyester
- 7/8 O.D. stem or 7/32" chain is provided in length as required for specified overall suspended height

### Electrical

- Integral multiple-lamp electronic ballasts are wired for 40 watt long compact or 32 watt T8 fluorescent lamps
- Lamps may be split into two circuits for remotely switched two-level illumination
- 120V-277V electronic ballasts are standard (347V optional)
- Optional single incandescent reflector lamp downlight has concentric louver assembly below for glare control
- Mounting plate above canopy mounts to ceiling structure and covers junction box
- Loop on stem meets seismic requirements

**Romanesque**  
*illustrated*



Hexagon 18" across points x 36"H  
(457 x 914mm)

**CH 160-4** illustrated  
with options:  
*Romanesque Design -ROM*  
*Downlight -DL*  
*Extended Top -ET*  
*Stem Suspension -STM*  
*Finish Color -ABZ*

**Gothic**  
*illustrated*



Hexagon 18" across points x 60"H  
(457 x 1524mm)

**CH 162-4** illustrated  
with options:  
*Gothic Design -GTH*  
*Decorative Banding -DB*  
*Hanging Yoke -HK*  
*Flared Tips -FT*  
*Chain Suspension -CHN*  
*Finish Color -ABZ*

### Catalog Number

Lamps	4 lamps	6 lamps	8 lamps	9 lamps
40W compact fluorescent (FT40W/2G11/RS)	<b>CH 160-4</b>	<b>CH 160-6</b>	<b>CH 160-8</b>	
32W T8 fluorescent (F32T8)	<b>CH 162-4</b>	<b>CH 162-6</b>	<b>CH 162-8</b>	
Six 100W A19 maximum incandescent		<b>CH 160-INC</b>		
Nine 100W A19 maximum incandescent				<b>CH 162-INC</b>
<i>Example: CH 162-4-GTH-DL-ET-ROM-STM-ABZ-SDY-98"</i>				

### Options

- Suspension:** Black chain: Add suffix **-CHN**.  
Black stem: Add suffix **-STM**.
- Finish Color:** Antique bronze vein: Add suffix **-ABZ**. Antique Copper Vein: Add suffix **-ACP**.
- Downlight:** Provides single medium base socket at bottom for 300 watt (max.) incandescent reflector lamp. Includes concentric louver in lieu of bottom diffuser. Add suffix **-DL**.
- Decorative Banding:** Adds detailed appearance. Add suffix **-DB**.
- Dimming Ballasts:** For use with Advance Mark X two-wire control system for 5%-100% range. Add suffix **-DIM**.
- Ballasts:** 277V, 347V. Add suffix **-277**, **-347**.

- Hanging Yoke:** Provides alternate connection from chain to fixture body. Not with **-ET**. Add suffix **-HK**.
- Extended Top:** Provides stepped top structure for alternate appearance. Not with **-HK**. Add suffix **-ET**.
- Flared Tips:** Provides extended and flared corner angles. Add suffix **-FT**.
- Romanesque Design:** Provides round arch. Add suffix **-ROM**.
- Gothic Design:** Provides peaked arch. Add suffix **-GTH**.
- Diffusers:** Alternates to standard white acrylic. Clear sandblasted glass: Add suffix **-GLS**. Sandblasted "seedy" glass: Add suffix **-SDY**. Other, as selected: Add suffix **-OS**.