

WB 170 Series



8 11/16" dia. W x 16"H x 4"D (221 x 406 x 102mm)
Dimming requires recessed housing 3 1/4"W x 2"D
x 11"H (83 x 51 x 279mm)

WB 170-118 illustrated

Construction

- Fixture is 20 gauge steel
- Diffusers are .125" white acrylic; other colors, textures, and materials are available
- 3/4" x 1" wood accents are stained golden oak unless otherwise specified

Electrical

- Integral electronic ballast is wired for one 18 or 24 watt compact fluorescent lamp (26 watt "quad" for dimming only)
- 120V-277V electronic ballasts are standard (347V optional)

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Lamps	1 lamp	2 lamps
18W (FT18W/2G11) compact fluorescent	WB 170-118	
24W (FT24W/2G11) compact fluorescent	WB 170-124	
60W T10 maximum medium base incandescent		WB 170-INC
<i>Example: WB 170-2-ABZ-277</i>		

Options

Dimming Ballasts: For CFQ26W/G24q-3 only: for use with Advance Mark X two-wire system for 5%-100% range. For other fixture models and dimming systems, inquire with factory.

Adds recessed housing.

Add suffix **-DIM**.

Diffusers: Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix **-ACR**.

Other, as selected. Add suffix **-OS**.

Delete Wood Accents: Add suffix **-DWA**.

Metal Channel Accents: Provides steel side channels in lieu of wood. Add suffix **-MCA**.

Ballasts: 277V, 347V. Add suffix **-277**, **-347**.



C. W. Cole & Company, Inc.
2560 N. Rosemead Boulevard
South El Monte, CA 91733-1593

Fax (626) 443-9253

Tel. (626) 443-2473

info@colelighting.com

www.colelighting.com