Interior/Exterior Applications



OPFN

PEN

34 1/2

(876mm)

Surface

34

(864mm)

Side-by-Side Readout

Catalog Numbers	
Wall	SL351-W
Ceiling	SL351-C
Recessed	SL351-R

Lamps

LED Green compartment (12.5 Watts) LED Red compartment (18.8 Watts)

Options

3 7/8

(98mm)

7" x 34"

(178 x 864mm)

3 7/8

7 1/2'

190mm)

Custom copy: Add suffix **-CC/** and specify copy requirement.

Flasher: For each compartment. Add suffix -FL.

The SL351 provides a low profile for mounting in surface or recessed locations with low clearance.

Signs

SL350 Series Two-compartment

SPECIFICATIONS

Construction

• Fixture is constructed of extruded aluminum with a black polyester coating • Graphic panels are .125" acrylic • Metal sunscreen is integral with faceplate • cULus listed, suitable for wet locations

Copy


Readout copy is not visible unless compartment is energized
Face has 4" (102mm) letters on bronze background
Standard copy is
OPEN in green and CLOSED in red
Custom copy is available


Electrical

 Wired for high output LED modules and universal voltage drivers
Separate circuit for each compartment

Mounting

 Surface sign mounts directly to recessed junction box, with four additional mounting holes
Recessed sign housing has holes in sides for mounting





Over/Under Readout

alog Number	
11	SL355-W
ling	SL355-C
cessed	SL355-R

Lamps

LED Green compartment (12.5 Watts) LED Red compartment (18.8 W)

Options

Custom copy: Add suffix **-CC**/ and specify copy requirement.

Flasher: For each compartment. Add suffix -FL.

The SL355 offers a compact format for surface or recessed mounting.



C.W. Cole & Company, Inc. 2560 Rosemead Boulevard South El Monte, CA 91733-1593

Tel. (626) 443-2473 Fax (626) 443-9253 info@colelighting.com www.colelighting.com