## JOB NAME

CATALOG NUMBER

#### 14-11/16 (127mm) (373 mm) KML-612-RED-AL-120 2-5/8" (67mm) 2-7/8" 2-3/4" (70mm) (178mm) 52mm) Surface Ceiling Side View -11-7/8" (302mm) KCL-612-GRN-A2-SBP-120 5"(127mm) → square - 2"-16-11/16" 2-7/8 (51mm) (424 mm) (73mm)14-11/16 (373 mm) 2-3/4" 0 Black (70mm) canopy and 18" stem · 5"(127mm) square are standard (178mm) for pendant Mounting mount canopy for Surface End pendant Front View -11-7/8" (302mm) KBL-612-RED-AR-277 14-11/16 (373mm) 5"(127mm) square 2-5/8" (67mm) 2-3/4" (70mm) SKCL-612-GRN-S1-CPY/WOMEN-SFT-277 (178mm) Mounting **Bracket** Surface Back |•|O|• Wallplate Side View -11-7/8" (302mm) -5"(127mm) -

SKCL-612-GRN-CPY/CUSTOM TEXT-SFT-CC/Black-277

TYPE

# Signs

# IRADITIONAL

Edgelighted Signs

# **K612/SK612 SERIES**

# **SPECIFICATIONS**

#### Construction

• Clear acrylic panel with green or red letters (6" for EXIT sign) and black backing . Single or double faced . Housing and bracket are cast aluminum with antique bronze vein powder coat . Not suitable for wet locations . Listed by ETL to UL 924 standard; meets NFPA Life Safety Code 101<sup>®</sup>.

## **Electrical**

· Red or green LEDs are dual-circuit and universal voltage • When emergency battery operation is specified, all components are contained in housing.

#### Mounting

Decorative cast bracket mounts to outlet box for ceiling, end, back, or mullion mounting.

# **How to Specify**

- 1. Select catalog number with desired features.
- 2. Add suffixes for options required to meet job conditions.

Catalog Numbers	Single Face				Double Face		
Lamps	Back	Ceiling	End	Mullion	Ceiling	End	
LED .4W (Red), .3W (Green)	☐ KWL-612	☐ KCL-612	☐ KBL-612	☐ KML-612	KCLD-612	☐ KBLD-612	
Custom copy (requires suffix)	SKWL-612	SKCL-612	SKBL-612	SKML-612	SKCLD-612	SKBLD-612	
Required suffixes	Letter color: ☐ RedRED. ☐ GreenGRN. Voltage: ☐ 1			Voltage: 120V	0V. <b>-120</b> . 277V. <b>-277</b>		
	Copy: Fill in your copy preference. Add suffixCPY/						

n	'n	ti	n	n	9
v	μ	u	u	ш	

### Directional arrows:

Arrow left, **\\_-AL**; Arrow right, **\\_-AR**;

Doublehead, \_\_\_-A2; Right and left (applies to double face only),  $\square$ -A.

Emergency battery operation:	Integral circuitry
provides 90 min. of operation.	Add suffix -EN

Special Font: Contact factory for custom font preference. Add suffix -SFT.

Pendant mount: Provides a black canopy and 18" **Clear Panel:** No black back. Add suffix \_\_-**CLR**. | stem. Use ceiling model number, add suffix \_\_-**S1** 

Bronze Finish: Satin	bronze p	ilated, c	lear (	coat
Add suffixSBP.				

Custom color: Alternate fixture housing and	
mounting brackets color. Add suffixCC/	
Pustom fant color: Custom painted font color	

Add suffixCFC/
/ / lad 5dill/