

JOB NAME


CATALOG NUMBER


Recessed





Pedestal





Catalog Numbers

rioccocca riodorig, corra rocoptació piato mai rocago barrior		
6" Pedestal housing, solid receptacle plate with voltage barrier	TL410-WCS-PED	
Installed Devices		
Weather resistant/tamper resistant receptacle	-GFCI	
Telephone or data connection in modular Decora® cutout	RJ11 orRJ45	
Universal Serial Bus port	USB	
High-definition multimedia interface	-HDMI	
Specify device to be installed or desired provisions-only	\square -9/(device or provisions)	
Specify device to be installed or desired provisions-only	-9/(indicate receptacle)	

Options

Bronze cover: Satin finished, clear coated.
(Recessed only) Add suffixB.
Pedestal height over 6": Add suffix -PED/(

Recessed housing, solid recentacle plate with voltage barrier

Pedestal height over 6": Add suffix 🔲 -PED/(height).	
ADA compliant pedestal: Add suffixPED/ADA.	

No key: Add suffix 🗌 -NK.
Custom color: Contact factory wit
preference Add suffix -cc.

TL410-WCS

TYPE

Plugging Box

TL410-WCS SERIES

SPECIFICATIONS

Construction

Cover is cast aluminum with self-closing, locking door • All units keyed alike • Cord slots backed with a rubber baffle system prevents the ingress of water • Recessed housing is 16 gauge electro-galvanized steel • Pedestal models are all aluminum • Cover and housing coated with metallic aluminum polyester powder coating


Electrical

Various wiring device combinations are available as indicated with catalog suffixes • Barrier provided between high and low voltage devices • Recessed housing has eight 1/2"- 3/4"-1"

• Recessed nousing has eight 1/2 - 3/4 - 1 combination trade-size knockouts • Pedestal allows for two conduit stub-ups • ETL listed while in use

Mounting

Recessed housing suitable for concrete pour. Pedestal models include anchor bolts



Pedestal Conduit Clearance

How to Specify

- 1. Select catalog number with desired features.
- 2. Add suffixes for options required to meet job conditions.



C.W. Cole & Company, Inc. 2560 N. Rosemead Boulevard South El Monte, CA 91733-1593

Tel. (626) 443-2473 Fax (626) 443-9253 info@colelighting.com www.colelighting.com