

JOB NAME _____

Type _____

CATALOG NUMBER _____

SC 160 Series

Specifications

Construction

• Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester

Electrical

• Integral multiple-lamp electronic ballasts are wired for four 13, 18, or 26 watt "quad" lamps on opposite sides of interior channel to be powered by each ballast • Lamps may be split into two circuits for remotely switched two-level illumination • 120V-277V electronic ballasts are standard

Gothic illustrated



Hexagon 24" across points x 9 1/2"H (610 x 241mm)

SC 160-426 illustrated
with options:
Gothic Design **-GTH**
Decorative Banding **-DB**
Flared Tips **-FT**
Finish Color **-ABZ**
Diffusers **-ACR**

Catalog Number

Lamps

4 lamps

13W (CFQ13W/G24q-1) "quad" compact fluorescent	<input type="checkbox"/> SC 160-413
18W (CFQ18W/G24q-2) "quad" compact fluorescent	<input type="checkbox"/> SC 160-418
26W (CFQ26W/G24q-3) "quad" compact fluorescent	<input type="checkbox"/> SC 160-426
60W T10 maximum medium base incandescent	<input type="checkbox"/> SC 160-INC

Example: SC 160-426-GTH-DB-FT-ABZ-ACR-277

Options

Dimming Ballasts: For SC 160-426 only: for use with Advance Mark X two-wire system for 5%-100% range. For other fixture models and dimming systems, inquire with factory. Add suffix **-DIM**.

Decorative Banding: Adds detailed appearance. Add suffix **-DB**.

Diffusers: Alternates to standard white acrylic. Clear sandblasted acrylic. Add suffix **-ACR**. Sandblasted "seedy" glass. Add suffix **-SDY**. Other, as selected. Add suffix **-OS**.

Finish Color:

Antique bronze vein: Add suffix **-ABZ**.
Antique Copper Vein: Add suffix **-ACP**.

Flared Tips: Provides extended and flared corner angles. Add suffix **-FT**.

Romanesque Design: Provides round arch. Add suffix **-ROM**.

Gothic Design: Provides peaked arch. Add suffix **-GTH**.



C. W. Cole & Company, Inc.
2560 N. Rosemead Boulevard
South El Monte, CA 91733-1593

Fax (626) 443-9253
Tel. (626) 443-2473
info@colelighting.com
www.colelighting.com