

**JOB NAME** \_\_\_\_\_

**Type** \_\_\_\_\_

**CATALOG NUMBER** \_\_\_\_\_

**WB 170 Series**



8 11/16" dia. W x 16"H x 4"D (221 x 406 x 102mm)

WB 170-118 illustrated

**Specifications**

**Construction**

- Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • 3/4" x 1" wood accents are stained golden oak unless otherwise specified

**Electrical**

- Integral electronic ballast is wired for one, 18, or 24 watt compact fluorescent lamp (26 watt "quad" for dimming only) • 120V-277V electronic ballasts are standard

**How to Specify**

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

**Catalog Number**

**Lamps**

1 lamp

2 lamps

18W (FT18W/2G11) compact fluorescent

**WB 170-118**

24W (FT24/27/2G11) compact fluorescent

**WB 170-124**

60W T10 maximum medium base incandescent

**WB 170-INC**

Example: WB 170-2-ABZ-277

**Options**

**Dimming Ballasts:** For CFQ26W/G24q-3 only: for use with Advance Mark X two-wire system for 5%-100% range. For other fixture models and dimming systems, inquire with factory.

Add suffix  **-DIM.**

**Diffusers:** Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix  **-ACR.**

Other, as selected. Add suffix  **-OS.**

**Delete Wood Accents:** Add suffix  **-DWA.**

**Metal Channel Accents:** Provides steel side channels in lieu of wood. Add suffix  **-MCA.**