



Church Lighting

160 Series

These Romanesque or Gothic-inspired hexagonal fixtures are available in several mounting configurations to allow a consistent design theme as various illumination needs are addressed. Multiple output options are available to meet job requirements. A variety of trim options are available that can be carried across the various models. Dimming capabilities available on all models.

These models can also be customized beyond the options illustrated to meet specific design goals.

COLE
Lighting

C.W. Cole & Company, Inc.
2560 Rosemead Boulevard
South El Monte, CA 91733-1593

Tel. (626) 443-2473
Fax (626) 443-9253
info@colelighting.com
www.colelighting.com

CH160 Series

Construction

- Fixture body and canopy are 20 gauge steel
- Flat diffuser provided in bottom unless other options are selected
- Diffusers are .125" white acrylic; other colors, textures, and materials are available
- Finish is textured powder coat polyester
- 7/8 O.D. black stem or 7/32" black chain is provided in length as required for specified overall suspended height.

Electrical

- Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%)
- LED options include E26/medium base, standard output and high output modules
- 120V-277V electronic drivers are standard universal voltage
- Optional downlight has concentric louver assembly below for glare control
- Mounting plate above canopy mounts to ceiling structure and covers junction box
- Loop on stem meets seismic requirements.

Romanesque illustrated

Hexagon
18" across points
x 36"H
(457 x 914mm)



CH160-LED illustrated
with options:
Romanesque Design **-ROM**
Downlight **-DL**
Extended Top **-ET**
Stem Suspension **-STM**
Finish Color **-ABZ**

Example:
CH160-LED-ROM-DL-ET-STM-ABZ-36"

Gothic illustrated

Hexagon
18" across points
x 60"H
(457 x 1524mm)



CH162-LED illustrated
with options:
Gothic Design **-GTH**
Decorative Banding **-DB**
Hanging Yoke **-HK**
Flared Tips **-FT**
Chain Suspension **-CHN**
Finish Color **-ABZ**

Catalog Number

Pendant	36"H	60"H
LED 96W, (8048 lm @ 3000°K)	CH160-LED	CH162-LED
LED 200W, (21168 lm @ 3000°K)	CH160-LED/HO	CH162-LED/HO
LED 144W, (12072 lm @ 3000°K)		
LED 300W, (31752 lm @ 3000°K)		
E26 medium base	CH160-LED/E26 (6 sockets)	CH162-LED/E26 (9 sockets)

Lumens shown are source. Church light photometric data available upon request.

Optional

Suspension: Black chain: Add suffix **-CHN**.

Black stem: Add suffix **-STM**.

Downlight: For E26 medium base LED reflector lamp. Add suffix **-DL**. For 34W at 3850 lumens, includes reflector. Add suffix **-DL/HO**.

Decorative Banding: Adds detailed appearance. Add suffix **-DB**.

Hanging Yoke: Provides alternate connection from chain to fixture body. Not with **-ET**. Add suffix **-HK**.

Extended Top: Provides stepped top structure for alternate appearance. Not with **-HK**. Add suffix **-ET**.

Flared Tips: Provides extended and flared corner angles. Add suffix **-FT**.

Romanesque Design: Provides round arch. Add suffix **-ROM**.

Gothic Design: Provides peaked arch. Add suffix **-GTH**.

Finish Color: Antique Bronze Vein. Add suffix **-ABZ**.
Antique Copper Vein. Add suffix **-ACP**.

Dimming: Universal voltage, 0-10V driver. 1%-100% range. Add suffix **-DIM**.

Remote Power Supply: Includes metal power supply/enclosure. Add Suffix **-REM**.

Diffusers: Alternates to standard white acrylic. Clear sandblasted acrylic. Add suffix **-ACR**. Clear sandblasted glass. Add suffix **-GLS**.

Sandblasted "seedy" glass (Recommended for E26 lamps only). Add suffix **-SDY**.

Other shielding, as specified. Add suffix **-OS/_____**.

LED colors:

2700°K (7807 lm), HO (24489 lm). Add suffix **-27K**.
4100°K (11710 lm), HO (36734 lm). Add suffix **-4K**.

SC160 Series

Gothic
illustrated



Hexagon
24" across points x 9-1/2"
H (610 x 241mm)

SC160-LED illustrated
with options:
Gothic Design -**GTH**
Decorative Banding -**DB**
Flared Tips -**FT**
Finish Color -**ABZ**
Diffusers -**ACR**

Example:
SC160-LED-GTH-DB-FT-ABZ-ACR

Romanesque
illustrated



SC160-LED illustrated
with options:
Romanesque Design -**ROM**
Finish Color -**ACP**
Diffusers -**GLS**

Example:
SC160-LED-ROM-ACP-GLS

Construction

- Fixture is 20 gauge steel
- Diffusers are .125" white acrylic; other colors, textures, and materials are available
- Finish is textured powder coat polyester

Electrical

- Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%)
- LED options include E26/medium base, standard output and high output modules
- 120V-277V electronic drivers are standard universal voltage.

Catalog Number

Surface Ceiling	Lamps
LED 25W, (2646 lm @ 3000°K)	SC160-LED
LED 50W, (5292 lm @ 3000°K)	SC160-LED/HO
E26 medium base	SC160-LED/E26 (4 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance.
Add suffix -**DB**.

Flared Tips: Provides extended and flared corner angles. Add suffix -**FT**.

Romanesque Design: Provides round arch.
Add suffix -**ROM**.

Gothic Design: Provides peaked arch.
Add suffix - **GTH**.

Finish Color:
Antique Bronze Vein. Add suffix -**ABZ**.
Antique Copper Vein. Add suffix -**ACP**.

Diffusers: Alternates to standard white acrylic.
Clear sandblasted acrylic. Add suffix -**ACR**.
Clear sandblasted glass. Add suffix -**GLS**.
Sandblasted "seedy" glass (Recommended for E26 lamps only). Add suffix -**SDY**.
Other shielding, as specified. Add suffix -**OS/_____**.

LED colors:
2700°K (7807 lm), HO (24489 lm). Add suffix -**27K**.
4100°K (11710 lm), HO (36734 lm). Add suffix -**4K**.

Dimming: Universal voltage, 0-10V driver.
1%-100% range. Add suffix -**DIM**.

WB160 Series

*Romanesque
illustrated*

8-1/2"W x 16"H x 4"D
(216 x 406 x 102mm)

Dimming requires
recessed housing
3-1/4"W x 2"D x 11"H
(83 x 51 x 279mm)



WB160-LED

Illustrated with options:

Romanesque Design -ROM

Finish Color -ABZ

Sandblasted "seedy"glass -SDY.

Example: WB160-LED-ROM-ABZ-SDY

Construction

• Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester

Electrical

• High performance LEDs are available in a variety of colors • Integral driver is standard universal voltage; optional 0-10v dimming driver available.

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Wall Sconce

Lamps

LED 12W, (1006 lm @ 3000°K)

WB160-LED

LED 25W, (2646 lm @ 3000°K)

WB160-LED/HO

E26 medium base

WB160-LED/E26 (2 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance.

Add suffix **-DB**.

Flared Tips: Provides extended and flared

corner angles. Add suffix **-FT**.

Romanesque Design: Provides round arch.

Add suffix **-ROM**.

Gothic Design: Provides peaked arch.

Add suffix **-GTH**.

Dimming: Universal voltage, 0-10V driver.

1%-100% range. Add suffix **-DIM**.

Voltage: 277V LED driver. Add suffix **-277**.

Finish Color:

Antique bronze vein. Add suffix **-ABZ**.

Antique Copper Vein. Add suffix **-ACP**.

LED colors:

2700°K (976 lm), HO (2567 lm).

Add suffix **-27K**.

4100°K (1030 lm), HO (2710 lm).

Add suffix **-4K**.

Diffusers: Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix **-ACR**.

Clear sandblasted glass. Add suffix **-GLS**.

Sandblasted "seedy" glass (Recommended

for E26 lamps only). Add suffix **-SDY**.

Other shielding, as selected.

Add suffix **-OS/_____**.



C.W. Cole & Company, Inc.

2560 Rosemead Boulevard

South El Monte, CA 91733-1593

Tel. (626) 443-2473

Fax (626) 443-9253

info@colelighting.com

www.colelighting.com