

SC160 Series

Gothic
illustrated



Hexagon
24" across points x 9 -1/2"
H (610 x 241mm)

SC160-LED illustrated
with options:
Gothic Design **-GTH**
Decorative Banding **-DB**
Flared Tips **-FT**
Finish Color **-ABZ**
Diffusers **-ACR**

Example:
SC160-LED-GTH-DB-FT-ABZ-ACR

Romanesque
illustrated



SC160-LED illustrated
with options:
Romanesque Design **-ROM**
Finish Color **-ACP**
Diffusers **-GLS**

Example:
SC160-LED-ROM-ACP-GLS

Construction

- Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester

Electrical

- Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%) • LED options include E26/medium base, standard output and high output modules • 120V-277V electronic drivers are standard universal voltage.

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Surface Ceiling

Lamps

LED 25W, (2646 lm @ 3000°K)	SC160-LED
LED 50W, (5292 lm @ 3000°K)	SC160-LED/HO
E26 medium base	SC160-LED/E26 (4 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance. Add suffix **-DB**.

Flared Tips: Provides extended and flared corner angles. Add suffix **-FT**.

Romanesque Design: Provides round arch. Add suffix **-ROM**.

Gothic Design: Provides peaked arch. Add suffix **-GTH**.

Finish Color:
Antique Bronze Vein: Add suffix **-ABZ**.
Antique Copper Vein: Add suffix **-ACP**.

Dimming: Universal voltage, 0-10V driver. 1%-100% range. Add suffix **-DIM**.

LED colors:
2700°K (7807 lm), HO (24489 lm) Add suffix **-27K**.
4100°K (11710 lm), HO (36734 lm) Add suffix **-4K**.

Diffusers: Alternates to standard white acrylic.
Clear sandblasted acrylic: Add suffix **-ACR**.
Clear sandblasted glass. Add suffix **-GLS**.
Sandblasted "seedy" glass (Recommended for E26 lamps only). Add suffix **-SDY**.

Other shielding, as specified. Add suffix **-OS/**_____ specify

COLE
Lighting

C.W. Cole & Company, Inc.
2560 Rosemead Boulevard
South El Monte, CA 91733-1593

Tel. (626) 443-2473
Fax (626) 443-9253
info@colelighting.com
www.colelighting.com