

## WB160 Series

*Romanesque  
illustrated*



8-1/2"W x 16"H x 4"D (216 x 406 x 102mm)  
Dimming requires recessed housing 3-1/4"W  
x 2"D x 11"H (83 x 51 x 279mm)

**WB160-LED**

*Illustrated with options:*

*Romanesque Design -ROM*

*Finish Color -ABZ*

*Example: WB160-LED-ROM-ABZ-SDY-277*

**Construction**

- Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester

**Electrical**

- High performance LEDs are available in a variety of colors • Integral driver is standard universal voltage; optional 0-10v dimming driver available.

**How to Specify**

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

**Catalog Number**

Wall Bracket	Lamps
LED 12W, (1006 lm @ 3000°K)	<b>WB160-LED</b>
LED 25W, (2646 lm @ 3000°K)	<b>WB160-LED/HO</b>
E26 medium base	<b>WB160-LED/E26</b> (2 sockets)

Lumens shown are source. Church light photometric data available upon request.

**Options**

**Decorative Banding:** Adds detailed appearance.

Add suffix **-DB**.

**Flared Tips:** Provides extended and flared corner angles. Add suffix **-FT**.

**Romanesque Design:** Provides round arch. Add suffix **-ROM**.

**Gothic Design:** Provides peaked arch. Add suffix **-GTH**.

**Dimming:** Universal voltage, 0-10V driver. 1%-100% range. Add suffix **-DIM**.

**Voltage:** 277V LED driver. Add suffix **-277**.

**Finish Color:**

Antique bronze vein: Add suffix **-ABZ**.

Antique Copper Vein: Add suffix **-ACP**.

**LED colors:**

2700°K (976 lm), HO (2567 lm).

Add suffix **-27K**.

4100°K (1030 lm), HO (2710 lm).

Add suffix **-4K**.

**Diffusers:** Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix **-ACR**.

Clear sandblasted glass. Add suffix **-GLS**.

Sandblasted "seedy" glass (Recommended for E26 lamps only). Add suffix **-SDY**.

Other shielding. Add suffix **-OS/** \_\_\_\_\_ *specify*



**C.W. Cole & Company, Inc.**  
2560 Rosemead Boulevard  
South El Monte, CA 91733-1593

Tel. (626) 443-2473

Fax (626) 443-9253

info@colelighting.com

[www.colelighting.com](http://www.colelighting.com)